

Technical Planning Aid In-roof

In order to submit an adequate offer, we require the information mentioned below. Please fill in the form and mail it to: sales@mounting-systems.com

1. Installation p	lace			Date:						
Street address:										
Postcode, place:										
Geographic Coordi	nates:									
Sea level:	ab	ove sea level (a.s.l.):		m						
Proximity to the sec	< 1000 m	> 1000 m								
2. Roof shape										
Double pitch		Mono pitch		Hipped roo	of (Hipped roof	_			
roof		roof		(long side)		(gable end)				
3. Building										
Roof pitch:			•	Building he			m			
(Inclination of the roof to the plain)			•	•	ound to the rid					
Gable pitch: (Only fill in when fixing	modules on g	able)		Roof area:	Length	Width	m			
4. Roof structur	e									
Rafter dimension:		Width	× Height		mm					
Rafter and purli	ns (only woo	d)			Com	olete sheeting (only wo	od)			
Dimensions of the purlins:		Length	Width _	mr	n Thick	ness of complete shee	ting: mm			
Distance of purlins:				m						
5. Flashing requ	uired									
Yes		No								
Colour of:	Visible pa	ırts:	Silver	Bla	ck					
	Sealing st	Sealing strip:		Ant	Anthracite					
6. Configuration	1									
Plant layout is	available (pl	ease attach)								
Direct connection to ¹ :		Verge left	Verge	right	Eaves	Ridge				
Module orientation	1	Portrait	Lands	cape						
Layout:	Row									
,	Column									
	Number o	of modules					pieces			

Technical Planning Aid In-roof



7. Module										
Module type ² :										
	Please attach the latest installation manual from the module, otherwise clamping assumed with standard clamp (for framed PV modules). Please attach the latest installation manual from the module, otherwise clamping assumed with standard clamp I=80 mm (for frameless PV modules).									
Module dimension	:	mm	×	mm	×		mm			
	Length		Width			Height				
Framed modu	ule	Framel	ess module							
Module weight:			kg							
Module power ou	tput:		Wp							
Clamp length:			mm							
Clamp points per	module:		pieces							
8 Optional										

Additional wishes

¹ Attention: Direct connections usually require special flashings, which are not included in the delivery of Mounting Systems GmbH. 2 Please add module datasheet including information about fixing restrictions.